

# Ceramite® Trowellable

Superior Performance in Wear Resistant Applications

Bulletin 0115

All Industries

06/03



## Attributes

- ↻ High abrasion and corrosion resistance
- ↻ Trowel application can be installed overhead
- ↻ Seamless linings
- ↻ Mechanical anchoring ensuring lining stability
- ↻ Will conform to whatever shape is required
- ↻ 1/2" - 1 1/4" thicknesses are sufficient
- ↻ Paddle mixer or 3/4" H.P. drill with Jiffler mixer
- ↻ One year shelf life
- ↻ Plastic bags to prevent moisture pickups - 55 lbs./bag - 40 bags/pallet

## INDUSTRIES SERVED

- |                 |                    |                        |                           |
|-----------------|--------------------|------------------------|---------------------------|
| ↻ Refining      | ↻ Non-Ferrous      | ↻ Zinc                 | ↻ Precast Manufacturing   |
| ↻ Rock Products | ↻ Die-Casting      | ↻ Boiler Manufacturing | ↻ Mineral Processing      |
| ↻ Chemical      | ↻ Power Generation | ↻ Primary Aluminum     | ↻ O.E.M. Furnace Builders |
| ↻ Steel         | ↻ Incineration     | ↻ Secondary Aluminum   | ↻ Cremation               |